

# BROADCAST PANEL

BROADCAST

SINGLE JOY STICK CONTROL PANEL

## ERGONOMIC DESIGN

PROVIDES PRECISE JOYSTICK AND FULL AXIS CONTROL



## MULTI-DEVICE CONTROL

WORKS WITH PTZs, ROBOTIC HEADS AND RAILS

## IP CONNECTION

FOR CONTROL OVER LOCAL OR WIDE AREA NETWORKS

The Broadcast Panel is specifically designed for broadcast environments. Supporting up to 12 cameras simultaneously, the control panel's buttons and controls are in a traditional broadcast layout allowing an operator to easily create and recall presets, whilst also having full control of all robotic axes, including speed and direction.

Operators can also control camera zoom and focus, again via familiar rocker and rotary controls.

# BROADCAST PANEL SPECIFICATIONS



IP  
CONNECTION



BUTTON MAPPING  
FUNCTION



MHC, FLAIR  
& ROBOKAM  
COMPATIBLE



## SPECIFICATIONS

<b>Weight</b>	2.8 kg / 6 lbs
<b>Height</b>	100 mm / 3.9 in
<b>Width</b>	420 mm / 16.5 in
<b>Length</b>	250 mm / 9.8 in

## PERFORMANCE

<b>Temperature Range</b>	-10 to +45°C
<b>Humidity Tolerance</b>	0% to 85% relative humidity, non-condensing
<b>Connection</b>	24V (power in) 3 Pin XLR Male 24V @ 1A USB Type A Service Port Ethernet RJ45 for IP connection