

PTA-1 ROBOTIC ARM

BROADCAST

ROBOTIC BROADCAST CAMERA PLATFORM



PAYLOAD
CAPACITY (KG)



IP65
RATED

OUTDOOR READY
DESIGNED FOR ALL WEATHER
ENVIRONMENTS



REMOVABLE CAMERA SLED
FOR EASY INSTALLATION

HIGH PAYLOAD CAPACITY
SUITABLE FOR LARGER BROADCAST
CAMERAS AND LENSES

The PTA-1 is a robotic camera platform specifically designed for supporting heavier broadcast cameras and lenses in outdoor applications. The high payload of the PTA-1 carries up to 25kg, giving customers more flexibility when deploying autonomous camera solutions.



A Nikon Company



MARK ROBERTS MOTION CONTROL

PTA-1 ROBOTIC ARM



FULL REMOTE
OPERATION/
PRODUCTION



EASY TO USE
CONTROL INTERFACE



QUICK TO USE
MODULAR SYSTEM



WEATHER PROOF
AND ROBUST



REMOTE PRODUCTION

This allows outside broadcasters to operate a camera in an environment where operators could not be easily positioned. The PTA-1 could then be operated from a truck or a remote location. With the IP65 rating, the system can be permanently installed in outdoor locations (stadiums, racecourses etc.) and due to its removable sled, any camera can be easily mounted and removed as required.

TECHNICAL INFORMATION

Size

- ▶ Operational space ~1.2 m³

Weight

- ▶ 15.3kg

Axes

- ▶ Pan max 180°/s (infinite movement)
- ▶ Tilt max 180°/s (+/- 45 ° movement)

Connections

- ▶ RJ45 (1000base-t)
- ▶ SDI (3G max. output 1080p 50/60 fps)
- ▶ Fibre optional plug in SFP for optical SDI output

Power

- ▶ Supplied with 240V 16A
- ▶ Optional 110V 16A and UK/EU/US



MARK ROBERTS MOTION CONTROL

MARK ROBERTS MOTION CONTROL

TELEPHONE: +44 (0)1342 838000

EMAIL: info@mrmoco.com

www.mrmoco.com/pta-1-robotic-arm

A Nikon Company

