

PTZ Monohead

BROADCAST

PARALLAX TRACKING FOR PTZ CAMERAS



FLEXIBLE APPLICATION
USE WITH ANY MPMC OR
SLIDEKAERMA BY MPMC RAIL

DESIGNED FOR PTZ CAMERAS
SUPPORTS A 16 KG / 35LB PAYLOAD

FIXED-POINT MOTION
WITH ROTATION SPEED 72°/S (360°/5S)

The PTZ Monohead enhances the horizontal axis motion for PTZ camera productions. The head provides fixed-point tracking for remote heads. Since PTZ cameras cannot perform this precise motion, the PTZ Monohead adds another panorama axis that replaces the horizontal movement by rotating the whole unit. Thanks to this simple trick, you can control the horizontal rotation of the kit, keeping all other benefits of your PTZ system.

PTZ MONOHEAD SPECIFICATIONS



FULL REMOTE
OPERATION



RELIABLE
PERFORMANCE &
REPEATABILITY



REPEATABLE
MOVES



ONE-BUTTON
TOUCH PRE-SET
RECALL



SPECIFICATIONS

Dimensions	Width: 317 mm / 12 in Depth: 136 mm / 5.3 in Height: 136 mm / 5.3 in
Mounting	Quick release mount option available
Inputs	HET-BUS & DC 36V: LEMO 6-pin Service Ports: 2 x USB-C Controller: mini-LEMO 4-pin (includes 12V power out for the controller)
Outputs	LCS mini-LEMO 6-pin
Power	24V to 36V DC max 120W + PDMOVIE (3 axes) max 40W

PERFORMANCE

Max. Payload	16kg / 35 lb
Rotation Speed	72°/s (360°/5s)
Axes	One
Available Set includes:	PTZ MONOHEAD STUDIO 1-axis remote head integrated AF-48 quick-release plate transport case LEMO cable (selected length)